

Decorative surface finishes for exterior applications



## PRODUCT INFORMATION

|                             |   |
|-----------------------------|---|
| <b>PRODUCT</b>              | <b>RENOLIT EXOFOL Professional Masking Tape</b>   |
| <b>Article number</b>       | Z0005.0017.00001 – <b>RENOLIT EXOFOL Professional Masking Tape</b>  |
| <b>Scope of application</b> | High quality UV-resistant masking tape. For the protection of surfaces laminated with <b>RENOLIT EXOFOL</b> films during painting and plastering. Suitable for both interior and exterior application. For industrial use only.   |
| <b>Technical Data</b>       | <p>Backing material : lightly crêped paper base, waterproof</p> <p>Type of adhesive : acrylic, UV stable</p> <p>Thickness : 170 µm</p> <p>Tensile strength : 33 N/cm</p> <p>Elongation at break : 5 %</p> <p>Temperature stability : up to +70 °C</p>   |
| <b>Specifications</b>       | <p>UV and weather resistant</p> <p>Ideal for intricate masking applications and where a sharp painted edge is required</p> <p>Easy to tear into required lengths</p> <p>Single masking applications allow multiple coats of paint to be applied</p> <p>Easy to remove without leaving adhesive residues</p> <p>No adhesive migration to the film surface</p> <p>Suitable for use with most types of paint, lacquers and woodstains</p> <p>Remove within three months of initial application</p> |
| <b>Misc.</b>                | <p>Blue colour</p> <p>Available in 50 linear metre rolls</p>  |



### RENOLIT EXOFOL Professional Masking Tape

Auf RENOLIT EXOFOL Folien abgestimmtes UV-Hochleistungs-Kreppband.  
High quality UV masking tape for RENOLIT EXOFOL laminated surfaces.

RENOLIT SE | Horchheimer Str. 50 | 67547 Worms | Germany  
Phone: +49.6241.94031-13 | Fax: +49.6241.94031-60  
folienservice@renolit.com | www.renolit.com/exteriorsolutions

Schützt das Profil bei Maler- oder Putzarbeiten. *Protects profiles during painting and plastering* | Für den Außen- und Innenbereich geeignet. *Suitable for both exterior and interior use* | Nach max. 3 Monaten entfernen. *Remove within 3 months* | Hohe mechanische Belastbarkeit durch Sonderdicke. *Special tape thickness provides excellent mechanical strength* | Migrations- und rückstandsfrei entfernbar. *Removable without migration or residues* | Nur für den industriellen Gebrauch. *For industrial use only.*

- |                              |                     |                        |
|------------------------------|---------------------|------------------------|
| Ⓢ Film de Masquage UV        | Ⓢ UV-afplakband     | Ⓢ маскіроўная лямпа    |
| Ⓢ Nastro per mascheratura UV | Ⓢ UV-afriekingstape | Ⓢ Тапіма маскіруюца UV |
| Ⓢ Cinta de enmascarar UV     | Ⓢ UV-Maskeringstejp | Ⓢ Клей пазка UV        |
| Ⓢ Fita de mascara UV         | Ⓢ UV-Maalrinteippi  | Ⓢ UV maskelerne bandi  |

Made in Germany | 30 mm x 50 m | Art.-Nr. Part No. Z0005.0017.00001

Status 10/2020

Market Unit Exterior Solutions  
exteriorsolutions@renolit.com  
www.renolit.com/exteriorsolutions  
www.renolit.com

RENOLIT SE  
Horchheimer Str. 50  
67547 Worms | Germany  
Phone: +49.6241.303.1040  
Fax: +49.6241.303.18.1139

RENOLIT Cramlington Limited  
Station Road  
Cramlington  
Northumberland, NE23 8AQ | United Kingdom  
Phone: +44.1670.718222  
Fax: +44.1670.590096



Rely on it.



## GENERAL PRODUCT INFORMATION

|  |  |
|--|--|
| <p><b>Application instructions</b></p> | <p>The substrate to be treated (film) must be dry, clean and free of grease prior to the application of the masking tape. We recommend cleaning the substrate with a dilute solution of soap, washing up liquid or any neutral, non-abrasive detergent. Abrasive cleaning agents or those containing unknown ingredients and/or solvents should not be used. The ingredients of solvent-based cleaning agents will damage the PMMA (polymethylmethacrylate) surface, which may not be immediately noticeable. This also applies to ethanol in its pure form.</p> <p>Apply <b>RENOLIT EXOFOL Professional Masking Tape</b> to a small, inconspicuous test area prior to application on larger surfaces.</p> <p>Apply <b>RENOLIT EXOFOL Professional Masking Tape</b> firmly in order to achieve full adhesion.</p> <p>To remove, peel off in a steady motion at an angle of 30-45 degrees. Do not use sharp tools or objects.</p> <p>For projects lasting more than three months, we recommend removing masking tape applied over three months previously and suitable cleaning of the substrate before reapplication of new masking tape.</p> <p><b>RENOLIT EXOFOL Masking Tape</b> should not be applied in damp conditions or building applications.</p> |
| <p><b>Storage</b></p>                  | <p>When stored in cool and dry conditions, <b>RENOLIT EXOFOL Masking Tape</b> is suitable for use for twelve months. Do not expose to excessive direct sunlight or frost.</p>  |
| <p><b>Chemical resistance</b></p>      | <p>Compatibility tests are always required. Please take into account that the chemical compatibility is strongly dependent on temperature, exposure time, concentration and state of aggregation of the substance.</p>   |
| <p><b>Care Instructions</b></p>        | <p>An appropriate cleaning after the removal of the masking tape should be performed, as explained above.</p>  |

For further information, please contact **RENOLIT**, Film Service: [folienservice@renolit.com](mailto:folienservice@renolit.com) . Phone: +49.6241.94031-13

This technical information sheet represents our latest state of knowledge and shall inform without obligation. The herein stated details do not release the manufacturer using our products from their own inspections and tests, which must correspond with the relevant national guidelines for its intended purpose. It is the duty of the customer to determine if the purchased product is suitable for its intended purpose.

**The recipient of this information shall neither forward nor publish the content or parts of it to any third parties without the prior written consent of RENOLIT.**

Status 10/2020

Market Unit Exterior Solutions  
exteriorsolutions@renolit.com  
www.renolit.com/exteriorsolutions  
www.renolit.com

**RENOLIT SE**  
Horchheimer Str. 50  
67547 Worms | Germany  
Phone: +49.6241.303.1040  
Fax: +49.6241.303.18.1139

**RENOLIT Cramlington Limited**  
Station Road  
Cramlington  
Northumberland, NE23 8AQ | United Kingdom  
Phone: +44.1670.718222  
Fax: +44.1670.590096



Rely on it.