


## PRODUCT INFORMATION

| PRODUCT              | Professional Cleaner for RENOLIT EXOFOL coated surfaces  |
|----------------------|--|
| Article number       | Z0007.0001.00002 – Professional Cleaner  |
| Scope of application | Special cleaner for <b>RENOLIT</b> EXOFOL coated surfaces For industrial use only                  |
| Chemical base        | Mixture of aliphatic hydrocarbons  |
| Delivery form        | 1000 ml Metal can with screw cap   |
| Ingredients          | Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5 % n-hexane, propan-2-ol, antistatic agent |



Stand 07/2024

Market Unit Exterior Solutions exteriorsolutions@renolit.com www.renolit.com/exteriorsolutions www.renolit.com

RENOLIT SE Horchheimer Str. 50 67547 Worms | Germany Phone: +49.6241.303.1040

Fax: +49.6241.303.18.1139

RENOLIT UK Limited
Station Road, Cramlington

Northumberland, NE23 8AQ | United Kingdom

Phone: +44.1670.718222 Fax: +44.1670.590096



Rely on it.

Decorative surface finishes for exterior applications



## **GENERAL PRODUCT INFORMATION**

| Description         | Professional Cleaner is a non-dissolving cleaner intended specifically for surfaces coated with <b>RENOLIT</b> EXOFOL laminates.  Grease remnants, adhesive residues, e. g. from protective film, abraded rubber from seals and dust can be removed. It has an anti-static effect which helps to prevent surfaces from becoming soiled again.   |
|---------------------|---|
| Application         | Observe the safety data sheet and wear eyeglasses with side panels and protective gloves. Apply cleaner to a dry, absorbent cloth made of cotton, wool or cellulose and clean the surface with the wet but not dripping cloth.  Note: Never treat or wipe RENOLIT EXOFOL surfaces in a dry state or by mechanical means, e. g. with rotating brushes. Do not use abrasive sponges or cloths. Remove heavy soiling with plenty of water before applying the cleaner. |
|                     | Avoid direct sunlight exposure during application.  Please consider, while cleaning, that the anti-static agent of the Professional Cleaner for <b>RENOLIT</b> EXOFOL coated surfaces r may impact negatively the bonding of sealant or glues.  |
| Storage             | Store in a closed container in cool and dry conditions. Expiration date is printed (see MHD) and has to be observed. Shelf life, after opening, is a maximum of 6 months.   |
| Safety indication   | For industrial use only. Information on ingredients, disposal and safety can be found in the safety data sheet as well as the precautionary statements on individual protective equipment.  The safety data sheets is available at <a href="https://www.renolit.com/professional-cleaner">www.renolit.com/professional-cleaner</a>  |
| Emergency telephone | Emergency telephone Berlin: +49 30 19 240 (bilingual German/English).  Important: Please find the local emergency telephone numbers in the safety data sheets at <a href="https://www.renolit.com/professional-cleaner">www.renolit.com/professional-cleaner</a>  |

For further information, please contact **RENOLIT**.

This technical information sheet represents our latest state of knowledge and shall inform without obligation. The herein stated details do not release the manufacturer using our products from their own inspections and tests, which must correspond with the relevant national guidelines for its intended purpose. It is the duty of the customer to determine if the purchased product is suitable for its intended purpose.

The recipient of this information shall neither forward nor publish the content or parts of it to any third parties without the prior written consent of RENOLIT.

Stand 07/2024

Market Unit Exterior Solutions exteriorsolutions@renolit.com www.renolit.com/exteriorsolutions www.renolit.com

RENOLIT SE Horchheimer Str. 50 67547 Worms | Germany Phone: +49.6241.303.1040 Fax: +49.6241.303.18.1139 RENOLIT UK Limited Station Road, Cramlington Northumberland, NE23 8AQ | United Kingdom

Phone: +44.1670.718222 Fax: +44.1670.590096

