



Decorative
surface finishes
for exterior
applications



PRODUCT INFORMATION

PRODUCT	Professional Cleaner for RENOLIT EXOFOL coated surfaces
Article number	Z0007.0001.00002 – Professional Cleaner
Scope of application	Special cleaner for RENOLIT EXOFOL coated surfaces For industrial use only
Chemical base	Mixture of aliphatic hydrocarbons
Delivery form	1000 ml Metal can with screw cap
Ingredients	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5 % n-hexane, propan-2-ol, antistatic agent



Status 07/2023


Market Unit Exterior Solutions
exteriorsolutions@renolit.com
www.renolit.com/exteriorsolutions
www.renolit.com

RENOLIT SE
Horchheimer Str. 50
67547 Worms | Germany
Phone: +49.6241.303.1040
Fax: +49.6241.303.18.1139

RENOLIT Cramlington Limited
Station Road
Cramlington
Northumberland, NE23 8AQ | United Kingdom
Phone: +44.1670.718222
Fax: +44.1670.590096



Rely on it.



GENERAL PRODUCT INFORMATION

Description	Professional Cleaner is a non-dissolving cleaner intended specifically for surfaces coated with RENOLIT EXOFOL laminates. Grease remnants, adhesive residues, e. g. from protective film, abraded rubber from seals and dust can be removed. It has an anti-static effect which helps to prevent surfaces from becoming soiled again.
Application	Observe the safety data sheet and wear eye glasses with side panels and protective gloves. Apply cleaner to a dry, absorbent cloth made of cotton, wool or cellulose and clean the surface with the wet but not dripping cloth. Note: Never treat or wipe RENOLIT EXOFOL surfaces in a dry state or by mechanical means, e. g. with rotating brushes. Do not use abrasive sponges or cloths. Remove heavy soiling with plenty of water before applying the cleaner. Avoid direct sunlight exposure during application. Please consider, while cleaning, that the anti-static agent of the Professional Cleaner for RENOLIT EXOFOL coated surfaces may impact negatively the bonding of sealant or glues.
Storage	Store in a closed container in cool and dry conditions. Expiration date is printed (see MHD) and has to be observed. Shelf life, after opening, is a maximum of 6 months.
Safety indication	For industrial use only. Information on ingredients, disposal and safety can be found in the safety data sheet as well as the precautionary statements on individual protective equipment. The safety data sheets is available at go.renolit.com/cleaner-sds
Emergency telephone	Emergency telephone Berlin: +49 30 19 240 (bilingual German/English). Important: Please find the local emergency telephone numbers in the safety data sheets at go.renolit.com/cleaner-sds

For further information, please contact **RENOLIT**.

This technical information sheet represents our latest state of knowledge and shall inform without obligation. The herein stated details do not release the manufacturer using our products from their own inspections and tests, which must correspond with the relevant national guidelines for its intended purpose. It is the duty of the customer to determine if the purchased product is suitable for its intended purpose.

The recipient of this information shall neither forward nor publish the content or parts of it to any third parties without the prior written consent of RENOLIT.

Status 07/2023

Market Unit Exterior Solutions
exteriorsolutions@renolit.com
www.renolit.com/exteriorsolutions
www.renolit.com

RENOLIT SE
Horchheimer Str. 50
67547 Worms | Germany
Phone: +49.6241.303.1040
Fax: +49.6241.303.18.1139

RENOLIT Cramlington Limited
Station Road
Cramlington
Northumberland, NE23 8AQ | United Kingdom
Phone: +44.1670.718222
Fax: +44.1670.590096



Rely on it.